

Murex Tradestig Dual 151i

This inverter offers superb DC arc welding characteristics for TIG welding from both 110v and 240v supplies. Features: non contact electric arc ignition with inbuilt gas pre-flow, current slope up time, adjustable current slope down and post flow times. Very portable weighing just 11kg. 2 year warranty

Technical Specification

Input	DUAL 1511
Voltage	230V/110V
Fuse	*16A/32A
Phase	1
Frequency	50/60Hz

Output

Current Range	10-150A
Rating TIG (230V)	150A/16V (60% Duty)
MMA (230V)	150A/26V (40% Duty)
Open Circuit Voltage	70V

Dimensions

Length mm	360
Width mm	155
Height mm	320
Weight kg (net)	11

Standards

EN60974 - 1
& EN50199

* On 230V supplies a 13A fuse is normally adequate

Comes with - TG 153 3.8 mtr Tig Torch, Accy Kit, Work Return Lead, Argon Reg, Argon Flowmeter, Gas Connection Kit, Manual



Price Beat!

- If you can find the models we list at a better price, ring us now! We'll try to beat it (Proof of price required)

migtigarc
SALES - HIRE - REPAIRS

TE/FAX 023 9229 5612
WWW.MIGTIGARC.CO.UK

261-263 MILTON ROAD, SOUTHSEA, HANTS P04 8PQ

Silver solder, welding curtains, gas rods, cutting & grinding discs, pickling paste, trolleys, safety footwear etc