

Sureweld Plasmacut 160HF Plasma Cutter

Robustly built and compact. The heavy duty transformer is designed to give excellent duty cycles making it suitable for heavy-duty use. Pilot arc system for smooth and reliable arc starting. Fan cooling and transformers with chopper technology give excellent duty cycles. Built-in air regulator and filter unit minimise problems caused by poor air supply. Pressure gauge and indicator lights show when machine is ready to cut. On-off switch and thermostatic overload protection. Amperage selection switch. Standard central connector for torch. Stylish TRAFIMET torch with 6 metre lead and safety trigger – the latest in plasma torch design giving a comfortable operating position with the ergonomically sculpted handle and head geometry. Interlock switch operated by the external nozzle ensures operator safety when changing torch consumables. Low cost consumables with long operating life. PLASMACUT 160E is fitted with the CBI50 torch
Two Year Warranty

Mains voltage	3ph V	400
Absorbed power	kWmax	25
Max no load voltage	V	250
Current range	A	20-160
Cutting current	A	160@40%
Max cutting thickness	mm	45
Air Flow required	L/min	200
Air Pressure reqd	bar	4-5
Dimensions LxWxH	870 x 590 x 860 mm	
Weight	kg	120



*Package Includes - 5 spare tips,
5 spare electrodes, 1 diffuser and 1 shroud*

Carriage Free

Price Beat!

- If you can find the models we list at a better price, ring us now! We'll try to beat it (Proof of price required)

migtigarc
SALES - HIRE - REPAIRS

TE/FAX 023 9229 5612
WWW.MIGTIGARC.CO.UK

261-263 MILTON ROAD, SOUTHSEA, HANTS P04 8PQ

*Silver solder, welding curtains, gas rods, cutting & grinding discs,
pickling paste, trolleys, safety footwear etc*