

Thermal Arc 150 TE

The 150TE is designed for HF TIG, LIFT-ARC TIG and STICK welding applications. This full function DC TIG and STICK machine comes as standard with adjustable pre-flow and post-flow gas control, slope down control and 2/4 step control.

MORE POWER TO YOU™

Features	Benefits
Thermal Overload Protection	Indicates temperature overload without damage to the machine
Automatic Arc Force	Easy striking, good arc stability and avoids electrodes "sticking"
High OCV : 80A – 90A	Easy striking and use of all types of stick electrodes
Automatic Hot Start	Clean positive arc striking
Slope Down	Controls current for end of weld crater fill
Input Voltage Protection	Protects the unit from damage from input fluctuation from generators

2 Years Warranty

Machine Specifications

Single Phase Power Supply	230v
Input Frequency	50 / 60 Hz
Fuse Rating	16A slow-blow
Maximum Power Consumption	5 KVA
Open Circuit Voltage	80A – 90A
Protection Factor	IP23
Insulation Class	H
Approvals	EN60 974-1-EN50.199



PROCESS	HF TIG	LIFT TIG	STICK		
Part Number	Rated Output @ Duty Cycle		Output Range	Dimensions (H x W x D)	Net Weight
10-9313	130A @ 60% 150A @ 35%		3 – 150 Amps	225 x 152 x 325 mm	7 kg

Price Beat!

- If you can find the models we list at a better price, ring us now! We'll try to beat it (Proof of price required)

migtigarc
SALES - HIRE - REPAIRS

TE/FAX 023 9229 5612
WWW.MIGTIGARC.CO.UK

261-263 MILTON ROAD, SOUTHSEA, HANTS P04 8PQ

Silver solder, welding curtains, gas rods, cutting & grinding discs, pickling paste, trolleys, safety footwear etc